

Capacity: 10 / 15 / 20 t

GD-2


Air hydraulic twin ram pit jack

- 2 individually controlled rams offer safe and balanced lifting
- Rapid and precise air hydraulic unit with high speed ram travel
- Simple modern design with control panel at ergonomical working height
- Transversely sliding rams
- Can be made to fit all pits due to its adjustable frame
- Frame height is adjusted and set to the customers individual specifications
- Comprehensive option range: cross beam, support bridge etc.
- Supplied with 2 x100 mm extensions
- *When ordering fill out specification form*



Technical data

	GD100-2	GD150-2	GD200-2
Capacity	10 t	15 t	20 t
Stroke	420 mm	420 mm	420 mm
Min. height	545 mm	545 mm	545 mm
Max. height	945 mm	945 mm	945 mm
Width ¹	590-1410 mm	590-1410 mm	590-1410 mm
Depth	649 mm	649 mm	649 mm
Lifting points ²	200-1160 mm	200-1160 mm	200-1160 mm
Air supply	8-12 bar	8-12 bar	8-12 bar
Air consumption	350 l/min	350 l/min	350 l/min
Weight	220 kg	220 kg	220 kg



¹ Framewidth: 590-890 mm / 850-1150 mm / 1110-1410 mm

² Distance between lifting points: 200-640 mm / 200-990 mm / 200-1160 mm

Accessories



